

Bookeye 3 – R1



Optical System

Maximum scan area:	900 x 630 mm / 35.5 x 24.8 inch
Scanner resolution:	400 x 400 dpi
Optical resolution:	300 x 400 dpi
Autofocus range	120 mm / 4.7 inch
Max. document thickness	120 mm / 90 mm (without / with glass plate)
Color depth	36 bit color, 12 bit grayscale
Scan modes:	24 bit color, 8 bit indexed color
	8 bit grayscale,
	bitonal, photo mode
Camera	CCD Camera, 22,800 pixel



Electrical Specifications

This device is Energy Star compliant.



Voltage	100-240V AC
Frequency	50/60 Hz

Power Consumption

Stand-by	0.1 W
Self-test mode	150 W
Ready to scan, lamps off	105 W
Scanning	275 W
Pre-scan	170 W

Moving the book cradle (lamps off)

Both plates simultaneously	128 W
Single plate	108 W

Illumination System

Light source:	Two lamps with linear positioned white LEDs
Warm-up time:	None. Maximum brightness immediately after switch-on.
Temperature dependency	None
UV / IR emission:	None
Luminosity	4500 LUX (scanning)
	1000 LUX (stand-by, 300 sec.)
	0 LUX (stand-by, idle)
Lamp life time:	50,000 hours scanning time

Version: 1.0 Date created: March 2010 Revised: 11/2014



Dimensions and Weight

Scanner outer dimensions (without lamps)	1250 x 900 x 780 mm (H x W x D) 49.2 x 35.4 x 30.7 inch
Scanner outer dimensions (lamps attached)	1250 x 1500 x 780 mm (H x W x D) 49.2 x 59 x 30.7 inch
Weight of scanner, incl. glass plate	80.5 kg / 177.1 lbs.
Dimensions transport box (contains main body, camera head in separate box, lamps, camera neck, test target folder, assembly material, tools and cables)	600 x 1535 x 1115 mm (H x W x D) 23.6 x 60.4 x 43.9 inch
Weight of transport box	55.5 kg / 122.1 lbs
Total shipping weight	152 kg / 334.4 lbs

Book Cradle

Maximum load / book cradle plate 15 kg / 33 lbs

Version: 1.0 Date created: March 2010 Revised: 11/2014



Ambient Conditions

Operating temperature	+5 to +40 °C / +40 to +105 °F
Storage temperature	0 to +60 °C / +32° to +140 °F
Relative humidity	20 to 80% (non-condensing)
Ambient luminance	≤ 300 LUX
Noise level	< 50 dB(A) (Operating)
	< 30 dB(A) (Stand-by)

© 2005 – 2013 by Image Access GmbH, Wuppertal, Germany.

Printed in Germany. All rights reserved.

Reproduction in whole or in part in any form or medium without express written permission of Image Access is prohibited.

Scan2Net[®], WideTEK[®] and Bookeye[®] are registered trademarks of Image Access.

All other trademarks are the property of their respective owners.

Image Access reserves the right to change the described products, the specifications or documents at any time without prior notice.

For the most recent version, always check our web site <u>www.imageaccess.de</u> or <u>www.imageaccess.us</u> or the customer service portal at <u>portal.imageaccess.de</u>

Version: 1.0 Date created: March 2010 Revised: 11/2014